

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number  
WO 2004/053290 A1

(51) International Patent Classification<sup>7</sup>: E21B 37/00,  
33/12, 33/127

David [GB/GB]; 23 Macaulay Grange, Countesswells,  
Aberdeen AB15 8FF (GB).

(21) International Application Number:  
PCT/GB2003/005337

(74) Agent: KENNEDYS PATENT AGENCY LIMITED;  
Floor 5, Queens House, 29 St Vincent Place, Glasgow G1  
2DT (GB).

(22) International Filing Date: 8 December 2003 (08.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0228645.8 9 December 2002 (09.12.2002) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): SPE-  
CIALISED PETROLEUM SERVICES GROUP  
LIMITED [GB/GB]; Arnhall Business Park, Westhill,  
Aberdeen AB32 6UF (GB).


(84) Designated States (*regional*): ARIPO patent (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

(72) Inventor; and

(75) Inventor/Applicant (for US only): HOWLETT, Paul,

[Continued on next page]

(54) Title: DOWNHOLE TOOL WITH ACTUABLE BARRIER



(57) Abstract: A downhole tool for use in a cased or lined well bore (40), the tool including a barrier (36) arranged on an outer surface of the tool. The barrier may be of a resilient material so that it can be deformed on actuation to control the passage of fluid between the tool and the casing or liner. Fluid flow is thus selectively diverted through flow paths (22) in the tool. Embodiments are described for actuating the barrier by hydraulic means and for filtering the fluid within the flow paths.



ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,  
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,  
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*